

BULLETIN NO.	237
ISSUED:	July 22, 2015
REPLACES:	June 4, 2013

Product Information Bulletin

US Product Certification Listings

PlastiSpan®, DuroSpan™ and ENERGREEN® Insulation

PlastiSpan®, **DuroSpan™** and **ENERGREEN®** insulation are listed with Intertek for material properties in accordance with ASTM C578, **Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation**, and for surface burning characteristics in accordance with ASTM E84, **Standard Test Method for Surface Burning Characteristics of Building Materials**.

The Intertek certification mark below is used on labels and/or packaging to signify third party certification/quality control of Plasti-Fab EPS insulation in accordance with ASTM C578 and ASTM E84.



ASTM C578 Types	Classification or Rating		
	Max. Thickness	Flame Spread	Smoke Developed
I, VIII, II and IX	6 inches	20	300

Notes:

1. See Plasti-Fab Product Information Bulletin No. 208 for PlastiSpan insulation material properties ASTM C578 product types.
2. See Plasti-Fab Product Information Bulletin 269 provides a copy of ICC-ES Evaluation Report ESR-1587 for PlastiSpan Insulation meeting requirements of the International Building Code and International Residential Code.
3. See Plasti-Fab Product Information Bulletin No. 308 for ENERGREEN insulation material properties ASTM C578 product types.